

# Solis-(50-66)K-US-F

Solis Three Phase US Inverters



## Features:

- ▶ Max. efficiency 98.8% (CEC efficiency 98.4%) with ultra-low start up voltage
- ▶ Compact and lightweight design inside a corrosion-resistant NEMA 4X enclosure
- ▶ Designed for all commercial, industrial, and utility-scale applications
- ▶ Transformer-less three phase design with 480 Vac output
- ▶ Wide voltage range and low startup voltage
- ▶ Industry-leading 4 MPPT designs with fast (<5 sec.) MPPT response times
- ▶ Integrated Arc Fault Circuit Interrupt (AFCI) option
- ▶ RS-485 Modbus communication protocol with Wi-Fi interface
- ▶ Web-based data monitoring with downloadable Solis Mobile App
- ▶ 10 years standard warranty with extension options



## Ordering: Solis-(50-66K)-US-F

- LSW-SPRT (SunSpec MLRSD Transmitter)
- LSW-RSS (Tigo MLRSD Transmitter)
- SW (No Transmitter)

## Datasheet

Model Name	Solis-50K-US-F-XX*	Solis-60K-US-F-XX*	Solis-66K-US-F-XX*
<b>Input DC</b>			
Recommended max. PV power	75 kW	90 kW	90 kW
Max. input voltage		1000 V	
Rated voltage		720 V	
Start-up voltage		200 V	
MPPT voltage range		200-850 V	
Max. input current		4*28.5 A	
Max. short circuit current		4*55 A	
MPPT number/Max. input strings number		4/16	
<b>Output AC</b>			
Rated output power	50 kW	60 kW	66 kW
Max. apparent output power	50 kVA	60 kVA	66 kVA
Max. output power	50 kW	60 kW	66 kW
Rated grid voltage		3Φ/PE, 480 V	
Rated grid frequency		60 Hz	
Max. output current	60.2 A	72.2 A	79.4 A
Power Factor		>0.99 (0.8 leading - 0.8 lagging)	
THDi		<3%	
<b>Efficiency</b>			
Max. efficiency		98.8%	
CEC efficiency		98.4%	
<b>Protection</b>			
DC reverse-polarity protection		Yes	
Ground fault monitoring		Yes	
Anti-islanding protection		Yes	
Integrated AFCI (DC arc-fault circuit protection)		Yes	
Integrated DC switch		Yes	
Rapid shutdown		Yes	
<b>General Data</b>			
Dimensions (W*H*D)	SW: 24.9*40.4*14.7 in (633*1027*374 mm), LSW: 24.9*47.5*14.7 in (633*1206*374 mm)		
Weight (inverter/wiring box)	SW: 147 lbs (66.7 kgs)/35.4 lbs (16 kgs), LSW: 147 lbs (66.7 kgs)/43.4 lbs (19.7 kgs)		
Topology	Transformerless		
Self consumption (night)	<1 W		
Relative humidity	0-100%		
Operating ambient temperature range	-13°F to 140°F (-25°C to 60°C)		
Storage environment	-13°F to 176°F (-25°C to 80°C)		
Ingress protection	TYPE 4X		
Cooling concept	Intelligent redundant fan-cooling		
Max. operation altitude	13,120 ft (4000 m)		
Compliance	UL 1741, IEEE 1547, UL 1699B, UL 1998, FCC, UL 1741SA, California Rule 21, SRD-UL1741, CAN/CSA C22.2 107.1-1		
<b>Features</b>			
DC connection	4 knockout for 2" conduit at bottom and side, Fuse screw terminal (Copper 12-6AWG)		
AC connection	4 knockout for 2" conduit at bottom and side, OT terminal (Copper or aluminum 8-2AWG) Aluminum requires bi-metallic compatible terminal		
Display	LCD		
Communication	Modbus RTU (Sunspec compliant), RS485, Optional: Cellular, Wi-Fi		

\* **Ordering guidelines:** Determine the basic model from above and add your desired features as described on PG1  
Ex: Solis-50K-US-F-LSW-SPRT, (inverter internal Sunspec transmitter)